

Sr. No.	Industry	Parameter	Standards
1	2	3	4
<sup>1</sup> [18.	<b>OMITTED</b>		
19.	<b>CALCIUM CARBIDE</b>	Particulate Matter Emission  - Kiln  - Arc Furnace	250 milligramme per normal cubic metre.  150 milligramme per normal cubic metre.
20.	<b>CARBON BLACK</b>	Particulate matter Emission	150 milligramme per normal cubic metre.
21.	<b>COPPER, LEAD AND ZINC SMELTING</b>	Particulate Matter Emission in Concentrator  Emission of Oxides of Sulphur in Smelter & convertor	150 milligramme per normal cubic metre.  Off-gases must be utilized for sulphuric acid manufacture. The limits of sulphur dioxide emission from stock shall not exceed 4 kilogramme per tonne of concentrated (one hundred per cent acide produced).
22.	<b>NITRIC ACID (EMISSION OXIDES OF NITROGEN)</b>	Emission of Oxides of Nitrogen	3 kilogramme of oxides of nitrogen per tonne of weak acid (before concentration) produced.
<sup>2</sup> [23.	<b>SULPHURIC ACID PLANT</b>	Emission standards Limiting concentration in mg/Nm <sup>3</sup> , unless stated  Plant capacity for 100% concentration of Sulphuric Acid (tonne/day)	

<sup>1</sup> Sr. No.18 relating to "Aluminum" and entries relating thereto omitted by Rule 2(II) of the Environment (Protection) First Amendment Rules, 2006 notified by G.S.R. 46(E), dated 3.2.2006.

<sup>2</sup> Substituted by Rule 2(I) of the Environment (Protection) Third Amendment Rules, 2008 notified by G.S.R. 344(E), dated 7.5.2008.